



TUG®

TEXTRON 



## MT

RESILIENT MULTI-TASKER.



# TUG<sup>®</sup> MT

Crafted with precision, the TUG<sup>™</sup> MT was built to effortlessly handle heavy loads, making every task attainable. Its pushback capability ensures seamless aircraft handling, optimizing ground support operations. The TUG MT guarantees nimble and efficient movement leading to reduced turnaround times with a top speed of 15 mph [24.1 kph]. Experience effortless maneuvering with power steering allowing for precise control in harsh environments. The 4-wheel suspension ensures a smooth and stable ride, minimizing vibrations and maximizing operator comfort. Featuring a standard e-hitch, the TUG MT brings versatility to your operations, revolutionizing your ground handling experience. Embrace power, speed, and reliability with the TUG MT, where heavy load mobility meets peak performance.

### SHARED FEATURES

- 12V, Negative Ground Electrical System
- Standard E-Hitch
- LED Headlights, Taillights, Backup Lights, and Turn Signals
- Power Steering
- Bucket Seats
- Retractable Seat Belts

### OPTIONAL FEATURES

- Cab
- Backup Alarm
- LCD Display
- Additional Hitches to Fit Custom Specifications



KUBOTA WG3800	
CHASSIS POWER	
Model	MT-38
Type	Liquid-Cooled, In-Line, 4 Cylinder
Fuel	30 US Gal [113.6 L] 87 Octane
Displacement	230 CID [3.8 L]
Governed RPM w/ Full Load	2,600
Net Brake hp at Governed Speed	87 [64.9 kW]
Torque	177 lb-ft [240 Nm] @ 2,400 RPM
Transmission	GM 4LHD
Shifter	Electronic FNR Between Seats
DIMENSIONS	
Width	74 in [1,880 mm]
Length (w/o Hitches)	MT8: 127 in [3,226 mm] MT12: 133 in [3,378 mm] - 12,000 lbs DBP
Height (w/ Cab)	84 in [2,134 mm]
Height (w/o Cab)	60 in [1,524 mm]
Wheelbase	80 in [2,032 mm]
Ground Clearance	8.3 in [211 mm]
Outside Turning Radius	173 in [4,394 mm]
Tires	Standard: Front: 8 X 16.5 in, 8-Ply Rating Rear: 215/75R17.5
STANDARD EQUIPMENT	
Drive Axle	Heavy Duty 12,000 lb [5,443.1 kg] Capacity Axle w/ Drop Box
Brakes	4 Wheel Disc w/ Hydraulic Power Assist and Dual Master Cylinder
Suspension	4 Wheel Suspension Leaf Springs on Front Axle Coil Springs & Shock Absorber on Rear

	MT-8	MT-10
PERFORMANCE		
Drawbar Pull	8,000 lb [3,628.7 kg]	10,000 lb [4,535.9 kg]
GVW	9,500 lb [4,309.1 kg]	14,500 lb [6,577.1 kg]